



Au Natural Collection

Applications	Commercial & Residential
Gauge	.125" nominal (1/8") (3.0mm)
Class	Class III, Printed Film Vinyl Tile, Embossed Texture
Carton Quantity	36 square feet (Weight 38 lbs)
12"x 12" (305mm x 305mm)	Baystone, Cork, European Marble, Fusion, Grecian Slate, Hellenic Slate, Marmara, Maze, Metallx, Oriental Slate, Paros Stone, Solid Colors, Tuscany, Wave
4"x 36" (101.6mm x 914mm)	Bamboo, Empire Woodgrains
6"x 36" (152mm x 914mm)	Fantasy, Rustic Woodgrains
18"x 18" (457.2mm x 457.2mm)	Aegean Stone, Basketweave, Fantasy, Imaginary, Luminous, Metallx, Solid Colors, Terrastone
12"x 18" (305mm x 457.2mm)	Fantasy, Lineare, Thassos Slate
Wear Surface	.20 mil vinyl (.50mm), Clear PVC, Commercial Grade
Standard Specification	Solid Vinyl Tile ASTM F1700 , ISO 9001 and ISO 14001 certified
Air Quality	FloorScore Certified
Recycled Content	Pre-Consumer – 26%
Residual Indentation	ASTM F970 – No visible apparent indentation at 250 psi
Static Coefficient of Friction	ASTM D02047-93 – Average .66
Taber Abrasion Test	H18 Wheels, 1000 gram load exceeds 12,000 cycles
Critical Radiant Flux	Class 1, ASTM E-648, 0.45 w/cm2 or higher
Subfloors, Recommended	½" underlayment grade plywood, concrete
Subfloors, NOT Recommended	Particle board, Chi p board, Black Tar Paper, Masonite, Cushioned Sheet Goods
Adhesive Recommended	Allied #1 Premium Acrylic Adhesive for most installations. Call for exceptions when installing on non-conforming substrates, below grade installations or excessive/ direct heat installations.
Warranty	Ten year warranty, one year manufacturing defects guarantee – see full warranty information.